



FLOOR SAW



MACHINE PRINCIPLE

The cutting process is achieved by the cutting discs turning at high speed (with an 'up cutting' action) and the diamond in the blade grinding a cut in the floor.

DESCRIPTION

The trolley mounted floor saw is designed for light duty cutting and chasing applications. The cutting blade is fully enclosed in a heavy duty metal shroud with dust extraction port for 'Dust Free' safe operation.

FEATURES

- 'Up cutting' action resulting in constant cut depth and dust free cut.
- Fully enclosed cutting operation
- Adjustable depth of cut up to 45mm

APPLICATIONS

Toeing in prior to the application of Resdev's fully comprehensive range of epoxy and polyurethane flooring Systems and for reinstating expansion joints.

The method of preparation is dependent upon both the substrate and the type of product used. For further information please refer to Resdev's product specific datasheets, specification information and material safety data.



82dB (A)

1330 VACUUM MACHINE SPECIFICATION	
Height 890mm	Length 970mm
Width 301mm	Plug rating 32amp
Power 110v (Also available in 240v)	Vibration Level Less than 2.50m/s ²
Usage 8 hours+	

ACCESSORIES

1330 Vacuum Unit – 110V

- For a 'dust free' operation
- Includes: 10m of 50mm hose & hose connector

Disc cutter shield

- For fully enclosed, safe operation

Cutting Blades

- Economy
- Premium

Transformer x 2

- Dual socket 5kva 32 amp 110v

Extension cable

- 32amp 110v – 10m length