



TROLLEY MOUNTED GRINDER

MACHINE PRINCIPLE

The grinding process is achieved by the grinding disc which is secured to the head and rotates in a circular motion.

DESCRIPTION

The Trolley mounted grinder has been specifically designed for use in confined areas where larger plant cannot reach. With contractors becoming increasingly aware of the importance of operators' health, safety and welfare, trolley mounted options have been developed to avoid time spent on hands and knees and benefit from the handle adjustment feature which allows for preparation under racks and plant.

FEATURES

- Steel dust shroud for connection to vacuum unit, for dust free operation and pollution control
- Edge grinding tool
- Quick assembly/disassembly
- Portable & compact

APPLICATIONS

Laitence and paint removal, levelling uneven surfaces and edge preparation prior to the application of Resdev's fully comprehensive range of epoxy and polyurethane flooring systems.

The method of preparation is dependent upon both the substrate and the type of product used. For further information please refer to Resdev's product specific datasheets, specification information and material safety data.



88dB (A)



| TROLLEY MOUNTED GRINDER MACHINE SPECIFICATION | |
|---|----------------|
| Height 1050mm | Length 900mm |
| Width 400mm | Weight 35kg |
| Working Width 180mm | Power 230v |
| Vibration Level Less than 2.50m/s ² | Usage 8 hours+ |

ACCESSORIES

1330 Vacuum Unit – 110V

- For a 'dust free' operation
- Includes: 10m of 50mm hose & hose connector

Metal dust shroud

- Connects to vacuum unit

Turbo Diamond Grinding Discs – 24 segment

- Blue – for use on soft materials
- Red – for use on hard materials

Transformer x 2

- Dual socket 5kva 32 amp 110v

Extension cable

- 32amp 110v – 10m length