



SAFETY DATA SHEET

Page 1 of 4

Pumaprime SF (Resin Component)

Revision 3
Revision date 19-Mar-2007

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Pumaprime SF (Resin Component)
Company Resdev Ltd
Pumaflor House
Ainleys Industrial Estate
Elland
HX5 9JP
info@resdev.co.uk
www.resdev.co.uk
Telephone +44 (0)1422 379131
Fax +44 (0)1422 370943

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Bisphenol A-(epichlorhydrin) (reaction product)	70 - 80%	25068-38-6	500-033-5	Xi; R36/37/38 R43 N; R51/53
Nonylphenol	1 - 10%	25154-52-3	246-672-0	Repr Cat 3; R62 Repr Cat 3; R62 Xn; R22 C; R34 N; R50/53
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	1 - 10%	108-65-6	203-603-9	R10 Xi; R36
Glycidylether of a C12/C14-alcohol mixture	10 - 20%	68609-97-2	271-846-8	Xi;R36 Xi;R38 Xi;R43 N;R51/53

3. HAZARDS IDENTIFICATION

Main hazards Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility. Possible risk of harm to the unborn child.

4. FIRST AID MEASURES

Skin contact Seek medical attention if irritation or symptoms persist. Wash off immediately with plenty of soap and water. Remove contaminated clothing.

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Move the exposed person to fresh air.

Ingestion Immediate medical attention is required. DO NOT INDUCE VOMITING.

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO₂). Sand.
Do NOT use dry chemical. Water jet, foam, ..

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear: Self-contained breathing apparatus.

Pumaprine SF (Resin Component)

Revision 3
Revision date 19-Mar-2007

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Do not flush into surface water. Do not let product contaminate subsoil.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean area thoroughly with detergent.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin.
Storage	Store at temperatures between 10 °C and 30 °C. Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 274 WEL 15 min limit mg/m3: 548
---	---	--

Engineering measures	Ensure adequate ventilation of the working area.
Occupational exposure controls	Keep away from food, drink and animal feedingstuffs.
Respiratory protection	Wear: Suitable respiratory equipment.
Hand protection	Nitrile rubber gloves. Butyl rubber gloves.
Eye protection	Approved safety goggles.
Protective equipment	Protect clothing from contact with the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Cream.
Odour	Slight.
Relative density	approx. 1.10
Viscosity	Flow Time in 3mm ISO cup (ISO 2431) - 10 - 16 poise @ 20°C

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heating produces hazardous fumes.
Materials to avoid	Strong bases. Strong oxidising agents.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	No data is available on this product.
Sensitization	May cause sensitisation by skin contact.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available on this product.
Degradability	Not readily biodegradable.

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
Disposal of packaging	Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.

Pumaprime SF (Resin Component)

Revision 3
Revision date 19-Mar-2007

14. TRANSPORT INFORMATION

ADR/RID

UN 3082	Packing group III
Class 9	Hazard ID 90
Proper Shipping ENVIRONMENTALLY	
Name HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	

IMDG

UN 3082	Packing group III
Class 9	Marine pollutant .
EmS Code F-A S-F	

IATA

UN 3082	Packing group III
Class 9	Subsidiary risk -
Packing Instruction 914 (Cargo)	Maximum quantity 450 L
Packing Instruction 914 (Passenger)	Maximum quantity 450 L

15. REGULATORY INFORMATION

Labelling P5 - Contains epoxy constituents. See information supplied by the manufacturer.

Symbols Xn - Harmful; N - Dangerous for the environment



Risk phrases

- R36/38 - Irritating to eyes and skin.
- R43 - May cause sensitisation by skin contact.
- R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R62 - Possible risk of impaired fertility.
- R63 - Possible risk of harm to the unborn child.

Safety phrases

- S24 - Avoid contact with skin.
- S29 - Do not empty into drains.
- S37 - Wear suitable gloves.

Pumaprine SF (Resin Component)

Revision 3

Revision date 19-Mar-2007

16. OTHER INFORMATION

Text of risk phrases in Section 2	R10 - Flammable. R22 - Harmful if swallowed. R34 - Causes burns. R36 - Irritating to eyes. R36/37/38 - Irritating to eyes, respiratory system and skin. R38 - Irritating to skin. R43 - May cause sensitisation by skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R62 - Possible risk of impaired fertility.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
Revision	This document differs from the previous version in the following areas: 15 - symbols. 16 - text of risk phrases in Section 2.