



## SAFETY DATA SHEET

Page 1 of 3

### Pumadur TZ Vertical Grade (Hardener Component)

Revision 8  
Revision date 30-Mar-2007

#### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

**Product name** Pumadur TZ Vertical Grade (Hardener Component)  
**Company** Resdev Ltd  
Pumafloor House  
Ainleys Industrial Estate  
Elland  
HX5 9JP  
info@resdev.co.uk  
www.resdev.co.uk  
**Telephone** +44 (0)1422 379131  
**Fax** +44 (0)1422 370943

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

##### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
4,4'-Diphenylmethane-diisocyanate	90 - 100%	9016-87-9		Xn;R20 Xi;R36 Xi;R37 Xi;R38 Xn;R42 Xi;R43

#### 3. HAZARDS IDENTIFICATION

**Main hazards** Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.

#### 4. FIRST AID MEASURES

**Skin contact** Wash with soap and water. Seek medical attention if irritation or symptoms persist.  
**Eye contact** Rinse immediately with plenty of water for 15 minutes holding the eyelids open.  
**Inhalation** Move the exposed person to fresh air. Seek medical attention.  
**Ingestion** DO NOT INDUCE VOMITING. Immediate medical attention is required. Rinse mouth thoroughly.

#### 5. FIRE FIGHTING MEASURES

**Extinguishing media** Carbon dioxide (CO2) Dry chemical. Alcohol resistant foam.  
**Fire hazards** Burning produces irritating, toxic and obnoxious fumes.  
**Protective equipment** Wear: Self-contained breathing apparatus.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions** Evacuate personnel to a safe area. Wear suitable protective equipment.  
**Environmental precautions** Prevent further spillage if safe. Do not allow product to enter drains. Advise local authorities if large spills cannot be contained.  
**Clean up methods** Remove mechanically; cover the remainder with wet, absorbent material (e.g. sawdust, chemical binder based on calcium silicate hydrate, sand). After approximately one hour transfer to waste container and do not seal (evolution of CO2!). Transfer to suitable, labelled containers for disposal.

Print date

6-Jun-2007

# Pumadur TZ Vertical Grade (Hardener Component)

Revision

8

Revision date

30-Mar-2007

## 7. HANDLING AND STORAGE

<b>Handling</b>	Ensure adequate ventilation of the working area. Do not eat, drink or smoke in areas where this product is used or stored. Avoid contact with eyes and skin.
<b>Storage</b>	Store at temperatures between 20 °C and 35 °C. Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Keep away from water.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering measures</b>	Ensure adequate ventilation of the working area.
<b>Occupational exposure controls</b>	Keep away from food, drink and animal feedingstuffs.
<b>Respiratory protection</b>	Wear suitable respiratory equipment when necessary.
<b>Hand protection</b>	Butyl rubber gloves. Neoprene gloves. Nitrile rubber gloves.
<b>Eye protection</b>	Approved safety goggles.
<b>Protective equipment</b>	Wash all contaminated clothing before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Description</b>	Liquid.
<b>Colour</b>	Amber.
<b>Odour</b>	Characteristic.
<b>Vapour pressure</b>	<0.00001 mmHg @ 25 °C
<b>Relative density</b>	1.21 - 1.25 @ 25 °C
<b>Water solubility</b>	insoluble.

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Conditions to avoid</b>	Heating produces hazardous fumes.
<b>Materials to avoid</b>	Acids. Amines. Bases. Strong oxidising agents. Copper and its alloys.

## 11. TOXICOLOGICAL INFORMATION

<b>Acute toxicity</b>	ORL RAT LD50 >2000 mg/kg. Ingestion may cause nausea and vomiting. Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible.
<b>Corrosivity</b>	May cause irritation to eyes. May cause irritation to skin. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
<b>Sensitization</b>	May cause sensitisation by skin contact.
<b>Repeated or prolonged exposure</b>	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Acute fish toxicity: LC50=>1000 mg/l 96H. Test species: Zebra barbel (Brachydanio rerio) Acute daphnia toxicity: EC50=> 1000 mg/l 24H. Test species: Daphnia magna.
<b>Degradability</b>	Not readily biodegradable, 0, 28.
<b>Further information</b>	The product reacts with water at the interface forming CO2 and a solid insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (e.g. detergents) or by water-soluble solvents.

# Pumadur TZ Vertical Grade (Hardener Component)

Revision 8


Revision date 30-Mar-2007

## 13. DISPOSAL CONSIDERATIONS

<b>General information</b>	Dispose of as special waste in compliance with local and national regulations.
<b>Disposal of packaging</b>	Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.

## 14. TRANSPORT INFORMATION

## 15. REGULATORY INFORMATION

<b>Labelling</b>	The product is classified in accordance with 67/548/EEC. P4 - Contains isocyanates. See information supplied by the manufacturer.
<b>Symbols</b>	Xn - Harmful 
<b>Risk phrases</b>	R20 - Harmful by inhalation. R36/37/38 - Irritating to eyes, respiratory system and skin. R42/43 - May cause sensitisation by inhalation and skin contact.
<b>Safety phrases</b>	S23 - Do not breathe gas/fumes/vapour/spray. S24 - Avoid contact with skin. S37 - Wear suitable gloves. S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S63 - In case of accident by inhalation: remove casualty to fresh air and keep at rest.

## 16. OTHER INFORMATION

<b>Text of risk phrases in Section 2</b>	R20 - Harmful by inhalation. R36 - Irritating to eyes. R37 - Irritating to respiratory system. R38 - Irritating to skin. R42 - May cause sensitisation by inhalation. R43 - May cause sensitisation by skin contact.
<b>Further information</b>	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
<b>Revision</b>	This document differs from the previous version in the following areas: 9 - viscosity.